

POINTS

1. How should hose couplings be cleaned? 20

2. What is done with out-of-round hose couplings? 20

3. How often should gaskets in hose couplings be inspected? 20

4. If coupling swivels need to be lubricated, what is used? 20

5. Name three (3) preventive measures which can be taken to limit damage to couplings. 20
 - a. _____
 - b. _____
 - c. _____

POINTS POSSIBLE: 100

POINTS DEDUCTED:

FINAL SCORE:

- | | <u>POINTS</u> |
|---|----------------------|
| 1. How should hose couplings be cleaned?

WITH WARM SOAPY WATER | <u>20</u> |
| 2. What is done with out-of-round hose couplings?

THROWN OUT/DISCARDED | <u>20</u> |
| 3. How often should gaskets in hose couplings be inspected?

ANNUALLY AND EACH TIME HOSE IS WASHED | <u>20</u> |
| 4. If coupling swivels need to be lubricated, what is used?

GRAPHITE | <u>20</u> |
| 5. Name three (3) preventive measures which can be taken to limit damage to couplings.

a. DO NOT DROP

b. DO NOT DRAG

c. COUPLE HOSE WHEN NOT USED TO PROTECT THREADS

DO NOT ALLOW VEHICLES TO DRIVE OVER THEM, DO NOT CROSS THREADS | <u>20</u> |

POINTS POSSIBLE: 100

POINTS DEDUCTED:

FINAL SCORE: